



DFCV-AD Q/S 9122

Previous generation products

Engineering data

REMARK: Do not use for construction. Refer to factory certified dimensions & weights. This page includes data current at time of publication, which should be reconfirmed at the time of purchase. In the interest of product improvement, specifications, weights and dimensions are subject to change without notice.

General notes

1. Adiabatic cooler capacities are tested according to EN 1048 for dry coolers.
2. TrilliumSeries Coolers of models with D6xx coil configuration have inlet and outlet connections at opposite ends.
3. Adiabatic pre-cooling sections are shipped separately and need to be installed on site.

Last update: 25/04/2024

DFCV-AD Q/S 9122



1. Fluid inlet connection; 2. Fluid outlet connection; 3. Pre-cooler water drain; 4. Electrical panel; 5. Pre-cooler city water connection.

Model	Nr. of Fans	Weights (kg)			Dimensions (mm)			Air Flow (m³/s) Δ	Tube Internal Volume (dm³)	Surface (m²)	Connections
		Oper. Weight (kg)	Ship. Weight(kg)	Heaviest Section (kg)	L	W	H				
DFCV Q9122-D613-D-AD	4	1950	1850	1450	2931	2730	2810	11.2	182.0	1488.0	2
DFCV Q9122-H613-D-AD	4	1950	1850	1450	2931	2730	2810	11.2	182.0	1488.0	2
DFCV Q9122-L613-D-AD	4	1950	1850	1450	2931	2730	2810	11.2	182.0	1488.0	2
DFCV Q9122-M613-D-AD	4	1950	1850	1450	2931	2730	2810	11.2	182.0	1488.0	2
DFCV Q9122-S613-D-AD	4	1950	1850	1450	2931	2730	2810	11.2	182.0	1488.0	2
DFCV S9122-D613-D-AD	4	1759	1491	1383	2931	2730	2810	21.2	182.0	1488.0	2
DFCV S9122-D616-D-AD	4	1981	1606	1498	2931	2730	2810	22.0	288.0	1336.0	2
DFCV S9122-H613-D-AD	4	1759	1491	1383	2931	2730	2810	21.2	182.0	1488.0	2
DFCV S9122-H616-D-AD	4	1981	1606	1498	2931	2730	2810	22.0	288.0	1336.0	2
DFCV S9122-L613-D-AD	4	1759	1491	1383	2931	2730	2810	21.2	182.0	1488.0	2
DFCV S9122-L616-D-AD	4	1981	1606	1498	2931	2730	2810	22.0	288.0	1336.0	2
DFCV S9122-M613-D-AD	4	1759	1491	1383	2931	2730	2810	21.2	182.0	1488.0	2
DFCV S9122-M616-D-AD	4	1981	1606	1498	2931	2730	2810	22.0	288.0	1336.0	2
DFCV S9122-S613-D-AD	4	1759	1491	1383	2931	2730	2810	21.2	182.0	1488.0	2



S613-D-AD											
DFCV S9122- S616-D-AD	4	1981	1606	1498	2931	2730	2810	22.0	288.0	1336.0	2