



DFCV-AD EC 9122

Previous generation products

Engineering data

REMARK: Do not use for construction. Refer to factory certified dimensions & weights. This page includes data current at time of publication, which should be reconfirmed at the time of purchase. In the interest of product improvement, specifications, weights and dimensions are subject to change without notice.

General notes

1. Adiabatic cooler capacities are tested according to EN 1048 for dry coolers.
2. TrilliumSeries Coolers of models with D6xx coil configuration have inlet and outlet connections at opposite ends.
3. Adiabatic pre-cooling sections are shipped separately and need to be installed on site.

Last update: 19/04/2024

DFCV-AD EC 9122



1. Fluid inlet connection; 2. Fluid outlet connection; 3. Pre-cooler water drain; 4. Electrical panel; 5. Pre-cooler city water connection; 6. Pre-cooler pads

Model	Nr. of Fans	Weights (kg)			Dimensions (mm)			Air Flow (m³/s)		Tube Internal Volume (dm³)	Surface (m²)	Connections
		Oper. Weight (kg)	Ship. Weight(kg)	Heaviest Section (kg)	L	W	H	Δ	Y			
DFCV EC912 2-D61 3-E- AD	4	1820	1520	1520	2752	2820	2735	23.3	23.3	182.0	1488.0	2
DFCV EC912 2-D61 6-E- AD	4	2040	1630	1630	2752	2820	2735	24.0	24.0	288.0	1336.0	2
DFCV EC912 2-H61 3-E- AD	4	1820	1520	1520	2752	2820	2735	23.3	23.3	182.0	1488.0	2
DFCV EC912 2-H61 6-E- AD	4	2040	1630	1630	2752	2820	2735	24.0	24.0	288.0	1336.0	2
DFCV EC912 2-L61 3-E- AD	4	1820	1520	1520	2752	2820	2735	23.3	23.3	182.0	1488.0	2
DFCV EC912 2-L61 6-E- AD	4	2040	1630	1630	2752	2820	2735	24.0	24.0	288.0	1336.0	2
DFCV EC912 2-M61 3-E- AD	4	1820	1520	1520	2752	2820	2735	23.3	23.3	182.0	1488.0	2
DFCV EC912 2-M61 6-E- AD	4	2040	1630	1630	2752	2820	2735	24.0	24.0	288.0	1336.0	2
DFCV EC912 2-S61 3-E- AD	4	1820	1520	1520	2752	2820	2735	23.3	23.3	182.0	1488.0	2
DFCV EC912 2-S61 6-E- AD	4	2040	1630	1630	2752	2820	2735	24.0	24.0	288.0	1336.0	2